

# Release notes

## Pro-10 2400 AirTTL

2017.02

Firmware version: B5



### General notes

### Pro-10 2400 AirTTL

The Pro-10 is designed to be “future proof” and the firmware can be upgraded via the USB port. Be sure to not miss important upgrades on your product. Register your Pro-10 on [Profoto.com/register](http://Profoto.com/register) to receive first-hand information of future upgrades on your product.

This release note covers firmware specific information. Detailed functionality descriptions are found in the user guide.

### New in firmware version B5

- Added HSS compatibility with Air Remote TTL-S version A3 (released 2017.02) and later versions.

### Check firmware version

When the Pro-10 is switched off, press and hold the settings knob [1] and press the ON button [2]. Release the settings knob and then turn the knob to “Show revision” and press down to select. The installed firmware version is displayed in the center display.



### Profoto Air Remote compatibility

The optional Profoto Air Remotes below are all tested with Pro-10 2400 AirTTL firmware version B5.

Profoto Air Remote options	TTL, HSS, Remote Control and sync	Remote Control and sync	Sync only
Air Remote TTL-C (For Canon)*	✓		
Air Remote TTL-N (For Nikon)**	✓		
Air Remote TTL-S (For Sony)***	✓		
Air Remote		✓	
Air Sync			✓

\* For the full list of tested Canon camera models, check latest release note for Air Remote TTL-C.

\*\* For the full list of tested Nikon camera models, check latest release note for Air Remote TTL-N.

\*\*\* For the full list of tested Sony camera models, check latest release note for Air Remote TTL-S.

Air Remote and Air Sync works with all cameras that have a hotshoe with ISO sync connection.